

GW-104A/B

SWIVEL MOUNT PHOTOCONTROL - PENCIL STYLE

The GW104 photocontrol comes with a swivel arm for easy reorientation of the photocontrol after installation. It fits in standard ½" knockouts in outlet boxes and wall-pack luminaires. They are made with UV-stabilized, high-impact, polycarbonate housings that stand up to outdoor environments. The GW104 uses the proven combination of a CdS sensor and a temperature-compensated, bi-metallic switch. It's designed to provide a long service life.



FEATURES

- Dusk-to-dawn control of outdoor lighting
- Floodlights and security lighting
- Rated for 1100W tungsten and 1800 VA ballast loads
- Ideal for LED fixtures totaling 600W @ 120 VAC
- Sealed CdS sensor
- Exceeds 3650 ON/OFF operations at full loads
- Meets the life expectancy of HID and LED fixtures
- UV stabilized black polycarbonate housing - Impact and drop resistant
- Easy to aim
- Low initial cost
- ANSI C136.24 compliant
- UL certified to UL773A



OPERATING SPECIFICATIONS

- Voltage: 110-120 or 200-240 VAC, 50/60Hz
- Dielectric strength: 2500 VAC
- Operating ambient temperature range: -40°C to 70°C
- Instant turn ON light level: 1.5 foot candle
- OFF light level: 5-10 foot candles
- Time delay: 20-90 seconds
- Fail mode: ON
- Power consumption: 1.5W @ 120 VAC
- 6" long, 18 AWG, 105°C copper wire leads

WARRANTY

- Limited 2-year manufacturer's warranty



5/13/2018